

Series datasheet — AT / ATTC Two-Stage Cone Type Pumps

Two-stage cone type liquid ring pumps in AT and ATTC configurations; verify the operating point and original drawing before selection.

vacuum@xiamenbest.com

Model	Capacity m³/h	Ult. pressure mbar	Motor kW	Speed rpm	Weight kg
AT706	1000	—	30	885	—
AT706	1100	—	30	980	—
AT706	1200	—	37	1050	—
AT1006	1485	—	45	690	—
AT1006	1615	—	55	730	—
AT1006	1955	—	75	880	—
AT1006	2040	—	90	980	—
AT2006	3010	—	90	500	—
AT2006	3310	—	110	550	—
AT2006	3570	—	110	590	—
AT3006	3740	—	110	400	—
AT3006	4420	—	160	450	—
AT3006	4760	—	185	500	—
AT100	—	—	—	—	—
AT1000	—	—	—	—	—
AT1300	—	—	—	—	—
AT133	—	—	—	—	—
AT1440	—	—	—	—	—
AT200	—	—	—	—	—
AT2000	—	—	—	—	—
AT253	—	—	—	—	—
AT2880	—	—	—	—	—
AT2940	—	—	—	—	—
AT300	—	—	—	—	—
AT3000	—	—	—	—	—
AT3600	—	—	—	—	—
AT400	—	—	—	—	—
AT410	—	—	—	—	—
AT438	—	—	—	—	—
AT8000	—	—	—	—	—

Capacity/other data may vary with speed and drive; confirm by drawing before ordering. NASH/SIHI are trademarks of their owners. We are an independent supplier.