

# Series datasheet — TXV Two-Stage Liquid Ring Vacuum Pumps

High-vacuum two-stage liquid ring pumps, 145–1589 m<sup>3</sup>/h, ultimate pressure 33 hPa, direct drive.

[vacuum@xiamenbest.com](mailto:vacuum@xiamenbest.com)

| Model   | Capacity m <sup>3</sup> /h | Ult. pressure mbar | Motor kW | Speed rpm | Weight kg |
|---------|----------------------------|--------------------|----------|-----------|-----------|
| TXV140  | 145                        | —                  | 4        | 1450      | —         |
| TXV180  | 186                        | —                  | 5.5      | 1450      | —         |
| TXV300  | 270                        | —                  | 7.5      | 1450      | —         |
| TXV350  | 342                        | —                  | 11       | 1450      | —         |
| TXV400  | 425                        | —                  | 15       | 1450      | —         |
| TXV500  | 501                        | —                  | 18.5     | 1450      | —         |
| TXV600  | 616                        | —                  | 22       | 1450      | —         |
| TXV800  | 862                        | —                  | 30       | 975       | —         |
| TXV1200 | 1252                       | —                  | 37       | 975       | —         |
| TXV1600 | 1589                       | —                  | 45       | 975       | —         |

Capacity/other data may vary with speed and drive; confirm by drawing before ordering. NASH/SIHI are trademarks of their owners. We are an independent supplier.